

Higher Quality Better Service!

We offer free update service for one year HTTP://WWW.PASSTCERT.COM

Exam : 922-089

Title : Communication Server RIs.5.0 Upgrades for Engineers

Version : DEMO

1. A customer is upgrading a Communication Server (CS) 1000E RIs. 4.5 system to a Communication Server (CS) 1000E RIs. 5.0 High Availability system. They wish to provide backup Terminal Proxy Server (TPS) services in case of a Signaling Server failure. Which component does not provide backup TPS services?

A. ITG-Pentium (ITG-P)

B. DSP Daughterboard

C. Media Card 32-port (MC32)

D. Media Card 32-port S (MC32S) Answer: B

A customer is upgrading an existing Communication Server (CS) 1000E at Rls. 4.5 to CS 1000E Rls.
High Availability (HA). The customer has decided to keep the CP-PII call processor. What is the maximum number of Media Gateway 1000E systems supported in this configuration?

A. 15

B. 25

C. 30

D. 50 Answer: C

3. A customer is upgrading an existing Communication Server (CS) 1000S at Rls. 4.5 to a CS 1000E Rls. 5.0 Standard Availability (SA) with a single Media Gateway 1000E chassis. As part of this upgrade, a CP-PM Call Server Card has been added. What happens to the Terminal Number (TN) format during the upgrade?

A. The format used by the small system (Card-Unit) is retained.

B. It is automatically converted to the large system format of Loop-Shelf-Card-Unit for IP Phones only.

C. It is automatically converted to the large system format of Loop-Shelf-Card-Unit for all assigned TNs.

D. It must be changed to the large system format of Loop-Shelf-Card-Unit through manually re-programming all devices assigned TNs. Answer: C

4. A customer is upgrading an existing Media Gateway (MG) 1000T to a Communication Server (CS) 1000E and maintaining it in autonomous (standalone) mode. What best describes this upgrade?

A. This upgrade is not a valid option in RIs. 5.0.

B. The MG 1000T Call Server is upgraded to a CP-PM Call Server and all other hardware remains.

C. The MG 1000T is upgraded to RIs. 5.0 maintaining all hardware but will require a new processor swap-out in the next release.

D. The MG 1000T SSC Gateway Controllers are replaced by Media Gateway Controllers, one CP-PM CS is added, and the PRI Cards are maintained. Answer: D

5. A customer is upgrading a Meridian 1 Option 81C Rls. 4.5 equipped with a CP4 processor to a Communication Server (CS) 1000M Multi-Group. Which option is available for the call processor?

A. CP-PM

B. CP PII

C. CP PIV

D. 68060E Answer: C