

PASSTCERT

QUESTION & ANSWER

Higher Quality
Better Service!

We offer free update service for one year
[HTTP://WWW.PASSTCERT.COM](http://www.passtcert.com)

Exam : CICSP

**Title : Cisco IronPort Certified
Security Professional
(CICSP) Web Security 7.0**

Version : Demo

1.The grep command can prompt you for the log file you want to search, and ask for other options.

- A. True
- B. False

Answer: A

2.For the WSA, HTTPS Inspection is enabled by default. ?

- A. True
- B. False

Answer: B

3.If a web site is blocked because it has a low web reputation score, which of the following is contained in the (un-customized) End-User Notification?

- A. The DVS engine verdict.
- B. The Treat Type.
- C. The web reputation score.
- D. The authenticated user, if authentication took place.

Answer: A

4.DRAG DROP

Match the port number to the use on the S-Series. Assume default ports are being used.

<div style="background-color: yellow; width: 100px; height: 20px; display: inline-block;"></div>	Traffic from the client to this port will be handled by the HTTP proxy.
<div style="background-color: yellow; width: 100px; height: 20px; display: inline-block;"></div>	This port is used for an HTTP connection to the administrative interface.
<div style="background-color: yellow; width: 100px; height: 20px; display: inline-block;"></div>	Traffic from the client to this port will be handled by the HTTPS proxy.
<div style="background-color: yellow; width: 100px; height: 20px; display: inline-block;"></div>	This port is used for an HTTPS connection to the administrative interface.
<div style="display: flex; justify-content: space-around; margin-top: 20px;"><div style="background-color: lightblue; padding: 5px 10px; border: 1px solid black;">8080</div><div style="background-color: lightblue; padding: 5px 10px; border: 1px solid black;">8443</div><div style="background-color: lightblue; padding: 5px 10px; border: 1px solid black;">443</div><div style="background-color: lightblue; padding: 5px 10px; border: 1px solid black;">80</div></div>	

Answer:

<div style="border: 2px solid red; padding: 2px; display: inline-block; background-color: lightblue;">80</div>	Traffic from the client to this port will be handled by the HTTP proxy.
<div style="border: 2px solid red; padding: 2px; display: inline-block; background-color: lightblue;">8080</div>	This port is used for an HTTP connection to the administrative interface.
<div style="border: 2px solid red; padding: 2px; display: inline-block; background-color: lightblue;">443</div>	Traffic from the client to this port will be handled by the HTTPS proxy.
<div style="border: 2px solid red; padding: 2px; display: inline-block; background-color: lightblue;">8443</div>	This port is used for an HTTPS connection to the administrative interface.
<div style="display: flex; justify-content: space-around; margin-top: 20px;"><div style="border: 2px solid green; padding: 5px 10px; background-color: lightblue;">8080</div><div style="border: 2px solid green; padding: 5px 10px; background-color: lightblue;">8443</div><div style="border: 2px solid green; padding: 5px 10px; background-color: lightblue;">443</div><div style="border: 2px solid green; padding: 5px 10px; background-color: lightblue;">80</div></div>	

5.CORRECT TEXT

What does DVS stand for?

Answer: Dynamic Vectoring and Streaming

6.The WSA can generate (on-box) reports and automatically email them to specified recipients.

- A. True
- B. False

Answer: A

7.In AsyncOS 7.0 for web the choice of Authentication Surrogate is a global setting.

- A. True
- B. False

Answer: B

8.The default IP address for the M1 interface on the WSA is_____.

- A. 192.168.42.42

Answer: A

9.Why does L4TM require T1 to be in promiscuous mode?

- A. To transmit TCP resets packets
- B. To process traffic not intended for its MAC address
- C. To receive Ethernet broadcasts
- D. To bind with other promiscuous mode ports

Answer: B

10.DRAG DROP

Match the interface with the use on the WSA

Can only be configured using the CLI					
Used by L4TM					
Used for proxy traffic when the customer uses in-band management					
Used for proxy traffic when the customer uses out-of-band management					
Never used					
M1	P1	M2	P2	T1	

Answer:

P2 Can only be configured using the CLI

T1 Used by L4TM

M1 Used for proxy traffic when the customer uses in-band management

P1 Used for proxy traffic when the customer uses out-of-band management

M2 Never used

M1

P1

M2

P2

T1