

PASSTCERT

QUESTION & ANSWER

Higher Quality
Better Service!

We offer free update service for one year
[HTTP://WWW.PASSTCERT.COM](http://www.passtcert.com)

Exam : HP0-S32

**Title : HP BladeSystem
Networking 2011**

Version : Demo

1.How can a tagged packet be processed for QoS when it is received on an inbound interface? (Select three.)

- A. The marked priority level can be changed to enforce predetermined classification levels.
- B. The packet can be scheduled for a queue based on the marked 802.1p priority level.
- C. The packet can be moved to a more secure VLAN and its priority remarked.
- D. The packet can be scheduled for a queue based on a preset policy.
- E. The packet can be discarded or rerouted if it does not match a set policy.
- F. The packet can be prevented switch traversal for a predetermined penalty period.

Answer: A, B, D

2.What are Virtual Connect Enterprise Manager features? (Select three.)

- A. is licensed per enclosure
- B. is licensed with the Virtual Connect Ethernet module
- C. is embedded on the Virtual Connect Ethernet module
- D. can administer up to 256,000 network addresses
- E. can manage a single domain of up to four enclosures
- F. can administer up to 16,000 servers

Answer: A, D, F

3.Which is a unique feature of a virtual switch?

- A. port mirroring for packet analysis
- B. VLAN segmentation at the port level
- C. no packet forwarding (routing) between VLANs
- D. maximum of 1016 ports per switch

Answer: D

4.What is considered a Virtual Connect domain in Virtual Connect Enterprise Manager?

- A. a maximum of 1,000 enclosures
- B. a maximum of 16,000 servers
- C. from 1 to 4 enclosures
- D. 250 Virtual Connect Manager domains

Answer: C

5.Which industry-standard protocols are supported on Virtual Connect Ethernet uplinks? (Select three.)

- A. IEEE 802.1 AX (802.3ad) Link Layer Discovery Protocol (LLDP)
- B. IEEE 802.1w-2001 Rapid Spanning Tree (RSTP)
- C. IEEE 802.1p Quality of Service (QoS)
- D. IEEE 802.1 AX (802.3ad) Link Aggregation Protocol
- E. IEEE 802.1Q VLAN tagging
- F. IEEE 802.3af-2003 Power over Ethernet (PoE)

Answer: A, D, E

6.Which tasks are used to define a vNet for Virtual Connect Ethernet? (Select three.)

- A. Assign only one network per server NIC.

- B. Assign one or multiple networks per server NIC.
- C. Optionally set the native VLAN.
- D. Define the server profile.
- E. Specify VLAN names/IDs.
- F. Select unassigned uplinks.

Answer: A, D, F

7.Which spanning tree protocol is the most appropriate in a VLAN-aware, non-proprietary network implementation?

- A. RSTP
- B. PVST+
- C. MSTP
- D. STP

Answer: C

8.The IEEE 802.1AX (802.3ad) Link Aggregation Control Protocol is a Layer 2 protocol. What is its function?

- A. dynamically identifies link speeds regardless of media type
- B. forms port trunks consisting of two or more uplink ports
- C. identifies the VLAN to which frames transmitted on a link or port trunk belong
- D. advertises information that describes and identifies devices

Answer: B

9.What is used to achieve Fibre Channel data transfer?

- A. channel mesh
- B. packets
- C. tunnels
- D. frames

Answer: D

10.What does N_Port ID virtualization do?

- A. provides an abstraction layer between the server HBAs and the SAN
- B. provides interoperability among third-party SAN device manufacturers
- C. provides connectivity between the Virtual Connect module and the Onboard Administrator
- D. enables a single HBA port to register multiple, unique WWNs within a fabric

Answer: D

11.What is considered a trunk in a Cisco switching environment?

- A. aggregated switch links
- B. tagged VLAN port (802.1Q)
- C. tagged VLAN port plus link aggregation
- D. Shared Uplink Set plus Connection Mode Auto

Answer: B

12. In a switching environment with redundant links, which technology is required for proper operation?

- A. VLANs
- B. Cisco vPC
- C. loop prevention
- D. dynamic routing

Answer: C

13. What are valid FlexNIC bandwidth selections? (Select three.)

- A. Preferred
- B. Assigned
- C. Static
- D. Custom
- E. Dynamic
- F. Auto

Answer: A, D, F

14. You are configuring Virtual Connect Flex-10 10Gb Ethernet modules with Flex-10 server adapters. What is an important network design consideration?

- A. The Virtual Connect Flex-10 10Gb Ethernet module does not enforce VLAN isolation between FlexNICs of the same server LAN on Motherboard (LOM).
- B. If the Flex-10 server adapters are implemented as mezzanine cards, the Virtual Connect Flex-10 10Gb Ethernet module requires all FlexNICs be configured for the same speed.
- C. The Virtual Connect Manager will enforce physical port isolation by not allowing FlexNICs of the same server port to connect to the same Virtual Connect network.
- D. LACP trunking is not allowed between Virtual Connect uplink ports and infrastructure switch ports located on different modules, even if within the same physical switch.

Answer: C

15. On a Cisco switch, what does the portfast setting do?

- A. eliminates auto-negotiation delays with 10GbE ports
- B. ensures the link is at maximum speed regardless of configuration
- C. causes BPDUs to be blocked if sensed
- D. eliminates delays inherent in RSTP/MSTP synchronization

Answer: D

16. What does trunk refer to in industry-standard terminology?

- A. aggregated switch links
- B. tagged VLAN port (802.1Q)
- C. tagged VLAN port plus link aggregation
- D. Shared Uplink Set plus Connection Mode Auto

Answer: A

17. Which statements are true about port VLAN memberships? (Select three.)

- A. A port can be an untagged member of multiple VLANs.

- B. A port must be a member of at least one VLAN.
- C. A port must be a tagged member of only one VLAN.
- D. A port can be an untagged member of only one VLAN.
- E. A port can be a tagged member of multiple VLANs.
- F. A port can be a tagged member of one VLAN and an untagged member of multiple VLANs.

Answer: B, D, E

18.What are the requirements for link aggregation using LACP? (Select three.)

- A. Links must have the same tagged VLANs assigned.
- B. Links must be the same speed.
- C. Links must use the same media type.
- D. Links must share a boundary.
- E. Links must be full-duplex.
- F. Links must be fiber connections.

Answer: B, D, E

19.What are valid reasons for implementing VLANs? (Select two.)

- A. to segregate traffic by resource or application needs
- B. to provide enhanced name resolution
- C. to reduce subnet cost options
- D. to minimize the effect of broadcast traffic on hosts
- E. to support multipathing

Answer: A, D

20.Which port is the lowest-cost path to the spanning tree root bridge?

- A. root port
- B. defined root port
- C. designated port
- D. forwarding port

Answer: A