PASSTCERT QUESTION & ANSWER

Higher Quality
Better Service!

We offer free update service for one year HTTP://WWW.PASSTCERT.COM

Exam : **HP2-K09**

Title : Supporting MSL2024 and

MSL4048 Tape Libraries

Version: Demo

- 1. Which SCSI signaling is supported with the MSL2024 and MSL4048 Tape Libraries? (Select two.)
- A. SE (single ended)
- B. SAS (serial attached SCSI)
- C. LVI (low voltage incremental)
- D. LVD (low voltage differential)
- E. HVD (high voltage differential)

Answer: BD

- 2. What is the maximum cable length on an LVD SCSI bus.?
- A. 9.84 ft (3 m)
- B. 19.68 ft (6 m)
- C. 39.37 ft (12 m)
- D. 82.02 ft (25 m)

Answer: C

- 3. What is the maximum native storage capacity of the MSL4048 Tape Library with an Ultrium 960 drive and all media slots loaded?
- A. 9.6 TB
- B. 19.2 TB
- C. 24.0 TB
- D. 36 TB

Answer: B

- 4. Which features are used by the LTO Ultrium tape family? (Select three.)
- A. cartridge memory
- B. global storage link
- C. adaptive tape speed
- D. adaptive compression
- E. adaptive cleaning heads
- F. media recognition system

Answer: ACD

- 5. Which tape drive format uses helical scan technology?
- A. AIT
- B. SDLT
- C. LTO-3
- D. Travan

Answer: A

- 6. What is the recommended maximum number of Ultrium 448 drives per SCSI bus when connected to an ULTRA320 HBA?
- A. 1
- B. 2

C. 3

D. 4

Answer: B

- 7. What is the maximum number of drives the MSL4048 can support? (Select two.)
- A. 2 Ultrium 960 tape drives
- B. 4 Ultrium 960 tape drives
- C. 4 Ultrium 448 tape drives
- D. 2 Ultrium 448 tape drives
- E. 2 Ultrium 448 tape drives and 1 Ultrium 960 tape drive in mixed configuration

Answer: AC

- 8. You are connecting an MSL2024 or MSL4048 library to a Fibre Channel SAN. Which statement is correct?
- A. One host only can have access to the tape devices.
- B. Each tape device can be accessed by only one host.
- C. All hosts can have shared access to the tape devices.
- D. Only hosts with HP Data Protector installed can share tape devices.

Answer: C

- 9. Which scheme reflects the slot numbering of an MSL2024 Tape Library?
- A. vertical columns from top to bottom, starting at the rear
- B. vertical columns from bottom to top, starting at the front
- C. horizontal rows from rear to front, starting at the top row
- D. horizontal rows from front to rear, starting at the bottom row

Answer: D

- 10. Which host interfaces (HBA) can be used for the tape drives of MSL2024 and MSL4048 Tape Libraries? (Select two.)
- A. Ultra 320 SCSI for the Ultrium 448 SCSI tape drive
- B. Ultra 320 SCSI for the Ultrium 960 SCSI tape drive
- C. 2Gb/s Fibre Channel HBA for the Native Fibre Channel Ultrium 960 tape drive
- D. 1Gb/s Fibre Channel HBA for the Native Fibre Channel Ultrium 960 tape drive
- E. 2Gb/s Fibre Channel HBA for the Native Fibre Channel Ultrium 960 tape drive

Answer: AB

- 11. Where are the magazines of an MSL2024 Tape Library located?
- A. at the left side with one mailslot
- B. at the right side with one mailslot
- C. at both sides with one mailslot at the left side
- D. at both sides with one mailslot at the right side

Answer: C

12. What is the host interface of the Ultrium 448 tape drive?

- A. Ultra 160 SCSI
- B. Ultra 320 SCSI
- C. 2Gb Fibre Channel
- D. 4Gb Fibre Channel

Answer: A

- 13. Which OCP parameters must be set before connecting to MSL2024 or MSL4048 libraries with RMI? (Select three.)
- A. network enabled
- B. service password
- C. web server enabled
- D. valid network settings
- E. administrator password
- F. serial connection enabled

Answer: ADE

- 14. Which HP tape solution provides 400GB native capacity with 80MB/s native performance?
- A. SDLT 320
- **B. SDLT 600**
- C. Ultrium 460
- D. Ultrium 960

Answer: D

- 15. Which HP tape drive solution incorporates WORM functionality? (Select two.)
- A. SDLT 600
- **B. SDLT 320**
- C. Ultrium 460
- D. Ultrium 960
- **E. DLT VS160**

Answer: AD