PASSTCERT
QUESTION & ANSWER

Higher Quality
Better Service!

We offer free update service for one year
HTTP://WWW.PASSTCERT.COM

Exam : HPE6-A75

Title : Aruba Certified Edge Professional Exam

Version : DEMO

1.cWhich technologies can prevent split brain in a VSF fabric that includes Aruba 2930F switches?
A. ARP MAD or OOBM MAD
B. VLAN MAD or ARP MAD
C. OOBM MAD or LLDP MAD
D. LLDP MAD or VLAN MAD
Answer: D

2.Refer to the exhibit.

Exhibit:accp67-543

Based on the configuration of the Enforcement Profiles In the Onboard Authorization service shown, which Onboarding action will occur?
A. The device will be disconnected from the network after Onboarding so that an EAP-TLS authentication is not performed.
B. The device will be disconnected from and reconnected to the network after Onboarding is completed.
C. The device's onboard authorization request will be denied.
D. The device will be disconnected after post-Onboarding EAP-TLS authentication, so a second EAP-TLS authentication is performed.
E. After logging in on the Onboard web login page, the device will be disconnected form and reconnected to the network before Onboard begins.
Answer: B

3.Refer to the exhibit.

Configuration » Authentication » Sources » Add - remotelab AD

Authentication Sources - remotelab AD

Summary | General | Primary | Attributes

Specify filter queries used to fetch authentication and authorization attributes

	Filter Name	Attribute Name	Alias Name	Enabled As
1.	Authentication	dn	UserDN	-
		department	Department	Role, Attribute
		title	Title	Attribute
		company	company	-
		memberOf	memberOf	Role, Attribute
		telephoneNumber	Phone	Attribute
		mail	Email	Attribute

Exhibit:accp67-312

Based on the Attribute configuration shown, which statement accurately describes the status of attribute values?

A. Only the attribute values of department and memberOf can be used in role mapping policies.

B. The attribute values of department, title, memberOf, telephoneNumber, and mail are directly applied as ClearPass.

C. Only the attribute value of company can be used in role mapping policies, not the other attributes.

D. The attribute values of department and memberOf are directly applied as ClearPass roles.

E. Only the attribute values of title, telephoneNumber, and mail can be used in role mapping policies.

Answer: D

4.An administrator wants to use Airwave to manually add devices on the network.

Where should the administrator perform this action?

A. in Device Setup

B. in Groups

C. in AMP Setup

D. in Devices

Answer: A

5.Refer to the exhibit.

```
Switch-1# show link-keepalive

 Status and Configuration - UniDirectional Link Detection (UDLD)

  Keepalive Retries  : 4
  Keepalive Interval : 5000 ms
  Keepalive Mode     : forward-then-verify

                Physical          Keepalive Adjacent          UDLD
  Port  Enabled Status            Status    Switch            VLAN
  ----- ------- ---------------- --------- ----------------- ----------
  A23   Yes     up                failure   00fd45-653ae9     untagged
```

Switch-1 and Switch-2 connect on interface A23. The switches experience a connectivity issue. The network administrator sees that both switches show this interface as up. The administrator sees the

output shown in the exhibit on Switch-1.
What is a typical issue that could cause this output?
A. a hardware issue, such as a broken cable
B. asymmetric routing introduced by a routing configuration error
C. an issue with queuing, caused by mismatched QoS settings
D. mismatched IP addresses on the VLAN for the link
Answer: A