

# PASSTCERT

QUESTION & ANSWER

Higher Quality  
Better Service!

We offer free update service for one year  
[HTTP://WWW.PASSTCERT.COM](http://www.passtcert.com)

**Exam** : **MA0-101**

**Title** : McAfee Certified Product  
Specialist – NSP

**Version** : Demo

1.Which port needs to be opened for Alert Channel communication between Sensor and Manager through a firewall?

- A. 8501
- B. 8502
- C. 8503
- D. 8555

**Answer: B**

2.Setting a threshold to allow an IPS to react when traffic volume exceeds the set limit is an example of what type of detection method.?

- A. Signature based
- B. Pattern matching
- C. Denial of Service
- D. Remediation

**Answer: C**

3.Performance debugging mode can be enabled on a sensor for a specified time duration by issuing which of the following CLI commands?

- A. sensor perf-debug 100
- B. sensor perf-debug on 100
- C. sensor perf-debug Interface all 100
- D. sensor perf-debug assert 100

**Answer: A**

4.What type of encryption is used for file transfers between the Sensor and the Manager?

- A. SSL with RC4
- B. SSL with MD5
- C. SSL with RC4 and MD5
- D. DES

**Answer: D**

5.When placed in Layer3 mode, a Sensor detects a Layer2 device based on which of the following?

- A. MAC address
- B. IP address
- C. DNS
- D. Subnet

**Answer: B**

6.What is the CLI command that enables the output of the MAC/IP address mapping table to the sensor debug files?

- A. arp spoof status
- B. arp spoof enable
- C. arp dump
- D. arp flush

**Answer: C**

7. DoS detection is implemented in which of the following modes? (Choose two)

- A. Learning mode
- B. Configuration mode
- C. Threshold mode
- D. Bidirectional mode
- E. Inbound mode

**Answer: A,C**

8. Which port needs to be opened for Packet Log Channel communication between Sensor and Manager through a firewall?

- A. 8501
- B. 8502
- C. 8503
- D. 8555

**Answer: C**

9. Which port is correctly defined for the Alert Channel on the Network Security Manager?

- A. 8500
- B. 8501
- C. 8502
- D. 8504

**Answer: C**

10. In double VLAN tagging, a second VLAN tag that is inserted into the frame is referred to as which of the following?

- A. Customer Identification tag (CD)
- B. VLAN Identification tag (VID)
- C. Outer Identification tag (OID)
- D. Inner Identification tag (HD)

**Answer: A**

11. Which of the following information is unique to Host Intrusion Prevention alerts? (Choose three)

- A. Destination IP
- B. User
- C. Source IP
- D. Agent IP
- E. Agent name

**Answer: B,D,E**

12. Which mode is used when certain hosts are located on the same network as a sensor and other hosts enter through a router or VPN?

- A. Mixed

- B. Hybrid
- C. Enforcement
- D. Prevention

**Answer: A**

13.Which mode needs to be set to redirect an unmanaged system to the guest portal?

- A. Audit
- B. Simulation
- C. Enforcement
- D. Prevention

**Answer: C**

14.Which attack cannot be blocked when the sensor has been set for in-line mode?

- A. TCP Control Anomaly
- B. ICMP Echo Anomaly
- C. Too Many Inbound Syn
- D. SCADA Attacks

**Answer: A**

15.Which database is supported for Network Security Manager?

- A. MSSQL
- B. Oracle
- C. MySQL
- D. Sybase

**Answer: C**